

HL460

PRODUCT SPECIFICATION SHEET

HIGH PERFORMANCE LIQUID CHROMATOGRAPHY Binary System



HPLC
Binary System

HL 460



Binary System



LCD Display



Flowcell



PC

Ideal for routine Binary separations and Quality assurance applications.

Our Economical HPLC systems are perfect for tight spaces and smart budgets.

Variable wavelength UV-VIS Detector features high sensitivity with absorbance ranges from 0 to 3.0 AU.

SALIENT FEATURES

- High performance Pulse free pump with low dead volume diaphragm type pulse damper.
- MS Windows® based software **Elichrom®** provides complete system control, Data Analysis and multiple reporting options.
- Self flushing, Pulse Damper with Pressure Monitoring.
- Connecting tubes available in Stainless steel or Bio compatible PEEK materials.
- Easy exchange of the Flow cells, Injection loops allows using the system for all applications between Micro upto preparative HPLC.
- Self diagnostics functions for start up hardware checks.
- Easy operatable Manual Injection Valve.
- An Autosampler, Fraction collector, Solvent Recycler can be easily added.
- Tools to facilitate 21 CFR part 11 compliance.



Pharmaceutical



Pesticide



Research



Chemical



Fertilizer



Food & Beverages



Clinical



Academic

APPLICATIONS

- Laboratories that demand Accuracy, Precision & reliability.
- Drug discovery, Drug metabolism, Proteins and Peptides Separations.
- Quality control labs in Pharmaceutical industries.
- Method development in R&D labs.
- Academic Institutes.

SPECIFICATIONS

HD 469

VARIABLE
UV-VIS DETECTOR

SPECTRAL

Range	190 to 800 nm
Bandwidth	4 nm
Readability	0.1nm
Accuracy	± 0.5 nm
Repeatability	± 0.2 nm

LIGHT SOURCE

Deuterium Lamp (D₂) &
Tungsten (W) Halogen Lamp

DATA PROCESSING & PRESENTATION

PC

PHOTOMETRIC

Range	0 to 3.0 AU
Drift	<2.0 x 10 ⁻⁴ AU/hr @254 nm
Noise	± 0.001 AU @254 nm, 1.0 sec. rise time
Sensitivity Range	0.001 AU to 3.000 AU
Readability	0.0001 Abs

DETECTOR

Silicon Photo Diode

PHYSICAL DIMENSIONS

Size (WxDxH) in mm	246* x 437 x 195
Weight (in kg)	Approx. 10

*Excluding 60 mm cell width

FLOW CELL

Type	Analytical
Path Length	10 mm
Volume	15 µl
Material	Stainless Steel

TIME INTERVAL

0.1, 0.2, 0.3, 0.4, 0.5, 1 & 2 sec.

PC CONNECTIVITY

USB Interface

POWER REQUIREMENT

90-260 V AC, 50-60 Hz, 1φ,
125 VA Max.

FLOW RATE

Standard	0.01 to 10 mL/min
Optional	0.001 to 5 mL/min
	0.1 to 40 mL/min

PHYSICAL DIMENSIONS

Size (WxDxH) in mm	246 x 437 x 140
Weight (in kg)	Approx. 11

HP 464

PUMP

QTY 2

PRESSURE

Standard	0 to 6,000 psi (10mL SS head)
Optional	0 to 6,000 psi (5mL SS head)
	0 to 5,000 psi (5 & 10 mL/min PEAK)
	0 to 1,600 psi (40 mL/min SS or PEAK head)

FLOW ACCURACY

± 2 %

FLOW PRECISION

0.2 % RSD

FEATURES

Pressure Monitoring
Prime Purge Valve
Pulse Damper
LED Display
RS-232 Input

POWER REQUIREMENT

90-260 V AC, 50-60 Hz, 1φ, 70 VA Max.

ACCESSORIES SUPPLIED

With Instrument	Columns, Injector, Mobile Phase Filter, Prime Purge Syringe, Injection Syringe.
At extra Cost	Other Applicable Columns & SGE Syringe and Sonicator.

Celebrating 60 years
of our Journey



www.elico.co/60years



www.elico.co

ELICO®

An ISO 9001:2018 | 14001 | 27001 Certified Company

B-90, A.P.I.E., Sanathnagar, Hyderabad 500 018, Telangana., India

Tel +91 40 44451234 Fax +91 40 23771639 info@elico.co

Ahmedabad

ahm@elico.co
+91 98241 75321

Bengaluru

blr@elico.co
+91 99000 28741

Bhopal

bpl@elico.co
+91 99930 96876

Bhubaneswar

bbr@elico.co
+91 99371 12105

Chennai

chn@elico.co
+91 98402 65797

Cochin

kel@elico.co
+91 81291 84400

Delhi

del@elico.co
+91 98710 06104

Guwahati

gau@elico.co
+91 91211 77451

Hyderabad

hyd@elico.co
+91 99896 25457

Kolkata

kol@elico.co
+91 91211 77452

Lucknow

lku@elico.co
+91 91980 01666

Mumbai

mum@elico.co
+91 77100 96111

Patna

pat@elico.co
+91 91211 77450

Visakhapatnam

vtz@elico.co
+91 99899 94532

